

V77E-RUR5

V77E Option Switch Settings : 1(Pulse/ICT/MDB)

Supported bill Ruble 10, 50, 100, 500, 1000

5bills.

V77E dip-switch settings and functions:

	FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
	Reject Ruble 10	ON											
★	Accept Ruble 10	OFF											
	Reject Ruble 50		ON										
★	Accept Ruble 50		OFF										
	Reject Ruble 100			ON									
★	Accept Ruble 100			OFF									
	Reject Ruble 500				ON								
★	Accept Ruble 500				OFF								
	Reject Ruble 1000					ON							
★	Accept Ruble 1000					OFF							
	Reserved						ON						
★	Reserved						OFF						
	Harness Disable							ON					
★	Harness Enable							OFF					
	Inhibit Active High								ON				
★	Inhibit Active Low								OFF				
★	1 pulse / Ruble 10									OFF	OFF		
	5 pulses / Ruble 10									ON	OFF		
	10 pulses / Ruble 10									OFF	ON		
	20 pulses / Ruble 10									ON	ON		
★	Pulse Speed	50ms on / 50ms off								OFF	OFF		
		60ms on / 300ms off								ON	OFF		
		30ms on / 50ms off								OFF	ON		
		150ms on / 150ms off								ON	ON		

★ Manufacture setting

◆ Factory configuration has all switches in the OFF position.

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW6.SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

V77E-RUR5 (Pulse/ICT/MDB)

Interface Settings: 2(Pulse)

	INTERFACE	SW1	SW2	SW3	SW4
★	Credit-Pulse Normal HIGH	ON			
	Credit-Pulse Normal LOW	OFF			
★	Pulse Interface		ON	OFF	
	ICT Interface		OFF	ON	
	MDB Interface		ON	ON	
★	Reserved				
					OFF

★ Manufacture setting

Interface Settings: 3(ICT)

	INTERFACE	SW1	SW2	SW3	SW4
★	Reserved	ON			
		OFF			
	Pulse Interface		ON	OFF	
★	ICT Interface		OFF	ON	
	MDB Interface		ON	ON	
★	Reserved				
					OFF

★ Manufacture setting

Interface Settings: 4(MDB)

	INTERFACE	SW1	SW2	SW3	SW4
★	Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
	Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
	Pulse Interface		ON	OFF	
	ICT Interface		OFF	ON	
★	MDB Interface		ON	ON	
★	Reserved				
					OFF

★ Manufacture setting